



Revised date 01.08.2025

MATERIAL SAFETY DATA SHEET CLEANING AGENT

CHEMICAL PRODUCT

Corporate MSDS Number : TAB-00200
Composition : Chemical Compound (99.9%)
Formula : Chemical Compound
UN# : 1078
HS Code : 382764
Hazard : 2.1

COMPANY IDENTIFICATION

TABRIGAS Egypt
Port Said Free Zone area – Egypt
Sunday – Thursday (9:00 – 17:00)
00 202 2734 22 77 / 78 / 79
info@tabrigas.com
www.tabrigas.com

PRODUCT USE

Cleaning agent for internal refrigeration circuits
Solvent

TRADE NAMES & SYNONYMS

Cleaning Agent (CA)

DIRECTIONS BEFORE USE

This is a specialized chemical, highly effective in **cleaning internal refrigeration circuits** and removing contaminants such as oil and grease. Avoid contact with painted surfaces, as **the product is a strong solvent and may damage paint.**

Safety Instructions

- Always wear appropriate personal protective equipment (PPE).
- Avoid inhalation of vapors and prevent contact with skin or eyes.
- Use only in well-ventilated areas.
- Follow occupational health and safety regulations strictly.

Revised date 01.08.2025

HAZARDS IDENTIFICATION

Emergency Overview

Clear, colorless liquid and vapor with a faint ether odor

WARNING!

Vapor reduces oxygen available for breathing. Harmful if inhaled and may cause heart irregularities, unconsciousness, or death. Nonflammable volatile liquid may cause eye irritation or drying of the skin. May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products.

Potential Health Effects

Skin contact and inhalation are expected to be the primary routes of occupational exposure to this material. Prolonged or repeated contact removes oils from the skin and may dry skin causing irritation, redness and rash. High vapor concentrations are irritating to the eyes and respiratory tract and may result in central nervous system (CNS) effects such as headache, dizziness, drowsiness and, in severe exposure, loss of consciousness and death. The dense vapor of this material may reduce the available oxygen for breathing. Prolonged exposure to an oxygen-deficient atmosphere may be fatal. Inhalation may cause an increase in the sensitivity of the heart to adrenaline, which could result in irregular or rapid heartbeats. Medical conditions aggravated by exposure to this material include heart disease or compromised heart function.

FIRST AID MEASURES

IF IN EYES, immediately flush with plenty of water for at least 15 minutes. Get medical attention. IF ON SKIN, flush the area with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops and persists. IF SWALLOWED, do NOT induce vomiting. Give water to drink. Get medical attention immediately. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Oxygen. Get medical attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this product.

FIRE FIGHTING MEASURES

Fire and Explosive Properties

Auto-Ignition Temperature	1022 °F / 550 °C
Flash Point	none Flash Point Method TCC
Flammable Limits- Upper	15.5
Lower	7.4

Extinguishing Media

Use water spray, water fog, carbon dioxide, or dry chemical

Revised date 01.08.2025

Fire Fighting Instructions

Cool fire-exposed containers well after the fire is out to prevent possible explosions. Firefighters and others who may be exposed to products of combustion should wear full firefighting turn-out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Firefighting equipment should be thoroughly decontaminated after use.

Fire and Explosion Hazards

May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Some mixtures of HCFCs and/or HFCs, and air or oxygen may be combustible if pressurized and exposed to extreme heat or flame. The container may explode if heated due to the resulting pressure rise.

ACCIDENTAL RELEASE MEASURES

In Case of a Spill or Leak

Use a Halogen leak detector or other suitable means to locate leaks or check the atmosphere. Keep upwind.

Evacuate enclosed spaces and disperse gas with floor-level forced-air ventilation. Exhaust vapors outdoors.

Do not smoke or operate internal combustion engines. Remove flames and heating elements.

HANDLING AND STORAGE

Handling

Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Keep the container closed. Use only with adequate ventilation. Wash thoroughly after handling. Keep away from heat, sparks, and flame. The emptied container retains vapor and product residue. Observe all labeled safeguards until the container is destroyed. Do not reuse this container. Do not cut or weld on or near this container.

Storage

Although this material is stable in long-term storage in carbon steel containers, it may gradually decompose in the presence of ferric chloride. The presence of excess levels of moisture, especially as a separate layer, should be avoided since it may lead to corrosion of carbon steel and formation of ferric chloride. It is recommended that containers be raised above floor or ground during extended storage periods to prevent container corrosion due to standing water. Before putting a storage system into service for this product, or after maintenance, ensure that the system is dry and oxygen-free. Purging the system with dry nitrogen is recommended. In addition, containers previously exposed to hydrogen chloride (for example, from impurities in chlorinated blowing agents or solvents), should be thoroughly cleaned first.

Revised date 01.08.2025

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Investigate engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to control exposure levels below airborne exposure limits (see below). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Eye / Face Protection

Where there is potential for eye contact, wear chemical goggles and have eye-flushing equipment Available.

Skin Protection

Wear appropriate chemical-resistant protective clothing and chemical-resistant gloves to prevent skin contact. Consult the glove manufacturer to determine the appropriate type of glove material for a given application.

Wear a face shield and chemical-resistant clothing such as a rubber apron when splashing may occur. Rinse contaminated skin promptly. Wash contaminated clothing and clean protective equipment before reuse.

Wash skin thoroughly after handling.

Respiratory Protection

Avoid breathing vapor or mist. When airborne exposure limits are exceeded (see below), use NIOSH-approved respiratory protection equipment appropriate to the material and/or its components. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Airborne Exposure Guidelines for Ingredients

Exposure Limit Value

8-hour TWA	500 ppm
WEEL TWA	500 ppm

-Skin contact limits designated with a "Y" above have a skin contact effect. Air sampling alone is insufficient to accurately quantify exposure. Measures to prevent significant continuous absorption may be required.

-ACGIH Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic reactions.

-WEEL-AIHA Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic skin reactions

Revised date 01.08.2025

PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor,	Clear, colorless liquid and vapor with faint ether odor
pH	NA
Specific Gravity	1.325 @ 25 °C
Vapor Pressure	10 psia @ 68 °F / 20 °C
Vapor Density	3.0
Melting Point	NA
Freezing Point	-154 °F / -103.5 °C
Boiling Point	38 - 39 °C
Solubility in Water	Slight
Percent Volatile	100

STABILITY AND REACTIVITY

Stability

This material is chemically stable under specified conditions or storage, shipment and/or use. See HANDLING AND STORAGE section of this MSDS for specified conditions.

Incompatibility

Avoid contact with hydrochloric acid, alkali or alkaline earth metals, finely powdered metals (aluminum, magnesium, zinc) and strong oxidizers since they may react or accelerate decomposition.

Hazardous Decomposition Products

Thermal decomposition products include hydrogen fluoride, hydrogen chloride, carbon monoxide, carbon dioxide, chlorine and carbonyl halides

TOXICOLOGICAL INFORMATION

Single exposure (acute) studies indicate

- Oral - Practically Non-toxic to Rats (LD50 >5,000 mg/kg)
- Dermal - No More than Slightly Toxic to Rats (LD50 >2,000 mg/kg)
- Inhalation - Practically Non-toxic to Rats (4-hr LC50 61,647 ppm)
- Eye Irritation - Non-irritating to Slightly Irritating to Rabbits

Skin Irritation - Non-irritating to Rabbits (4-hr and 24-hr exposures)

No skin allergy was observed in guinea pigs following repeated exposure. Inhalation of high concentrations produces a transient anesthetic effect in rodents. As with many other halogenated hydrocarbons, inhalation followed by intravenous injection of epinephrine to simulate human stress reactions resulted in heart sensitization in dogs and monkeys. Repeated inhalation studies resulted in minor changes in body weight and slight changes in blood chemistry in rats. Repeated inhalation of

Revised date 01.08.2025

vapor produced no evidence of nervous system toxicity or behavioral effects in rats. Long-term inhalation caused an increase in the incidence of benign, non-life-threatening tumors of the testes in rats. No birth defects were noted in the offspring of rabbits exposed by inhalation during pregnancy; signs of maternal toxicity were noted. No birth defects were noted in the offspring of rats exposed to inhalation during pregnancy; toxic effects were noted in the mothers and their offspring. In a reproduction study, reductions in litter size, total litter weight, and growth rate were observed in rats exposed to inhalation for 2 generations. Delayed sexual maturity of male offspring from exposed parents may have been related to the lower growth rate. Generally, no genetic changes were observed in tests using bacteria, animal cells, or animals. Metabolism studies in rats exposed by inhalation show that this material is not metabolized or accumulated in the body to any significant extent.

ECOLOGICAL INFORMATION

Eco toxicological Information

This material is slightly toxic to *Daphnia magna* (48-hr EC50 31.2 mg/l), rainbow trout (24-hr LC50 83.5 mg/l) or algae (EC50 67.8 mg/l). It is practically non-toxic to zebrafish (96-hr LC50 126 mg/l).

Chemical Fate Information

This material is not readily biodegradable (24% after 28 days). Based on its log Pow of 2.3, bioaccumulation is considered unlikely

DISPOSAL CONSIDERATIONS

Waste Disposal:

Recover, reclaim, or recycle when practical. Dispose of per federal, state, and local regulations. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

TRANSPORTATION INFORMATION

DOT Name	NOT REGULATED
DOT Technical Name	
DOT Hazard Class	
UN Number	
DOT Packing Group	PG
RQ	
DOT Special Information	Not regulated when shipped by ground, water, or air.

Revised date 01.08.2025

REGULATORY INFORMATION

Hazard Categories under Criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health Y	Fire	N
Delayed (Chronic) Health N	Reactive	N
	Sudden Release of Pressure	N

The components of this product are all on the TSCA Inventory list.

Ingredient Regulatory Information

SARA Reportable Quantities	CERCLA RQ	SARA TPQ
Cleaning Agent	NE	

SARA Title III, Section 313

This product does contain chemical(s) which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

End of MSDS
(Version August 2025)

