

Revised date 01.08.2024

MATERIAL SAFETY DATA SHEET HCFC 22

CHEMICAL PRODUCT

Corporate MSDS Number : TAB-002001
Composition : HCFC (100%)
Chemical Formula : CHClF_2
CAS# : 75-45-6
UN# : 1018
HS Code : 290371
Hazard : 2.2

COMPANY IDENTIFICATION

TABRIGAS Egypt
Port Said Free Zone area - Egypt
Sunday - Thursday (9:00 - 17:00)
00 202 2734 22 77 / 78 / 79
info@tabrigas.com
www.tabrigas.com

Product Use

Refrigerant
Propellant/Blowing Agent

Trade names and Synonyms

Chlorodifluoromethane
HCFC 22

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation of high concentrations of vapor is harmful and may cause heart irregularities, unconsciousness, or death. Intentional misuse or deliberate inhalation can be fatal. Vapors are heavier than air and pose a threat of suffocation if trapped in enclosed or low places. Liquid contact can cause frostbite. Inhalation may cause dizziness, headache, confusion, incoordination, and loss of consciousness.

Immediate effects of overexposure by inhalation may include central nervous system depression with dizziness, confusion, coordination, drowsiness, or unconsciousness. Gross overexposure may cause

Revised date 01.08.2024

irregular heartbeat with a strange sensation in the chest, "heart thumping", apprehension, lightheadedness, the feeling of fainting, dizziness, and weakness, sometimes progressing to loss of consciousness and death. Other effects include fatality from gross over-exposure.

Short-term overexposure by skin contact may cause frostbite if liquid or escaping vapor contacts the skin. Repeated and/or prolonged exposure may cause defeating of the skin with itching, redness, or rash. Data to evaluate the skin permeation hazard of this compound are insufficient. There are no reports of human sensitization. Contact with the vapor or aerosol may cause eye irritation with tearing, pain, or blurred vision. Increased susceptibility to the effects of this material may be observed in persons with pre-existing diseases of the central nervous system, and cardiovascular system.

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST-AID

Inhalation

If inhaled, immediately remove to fresh air. Keep the person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Skin Contact

In case of contact, flush the area with lukewarm water. Do not use hot water. If frostbite has occurred, call a physician.

Eye Contact

In case of contact, immediately flush your eyes with plenty of water for at least 15 minutes. Call a Physician.

Ingestion

Ingestion is not considered a potential route of exposure.

Notes to Physicians

THIS MATERIAL MAY MAKE THE HEART MORE SUSCEPTIBLE TO ARRHYTHMIAS. Catecholamine such as adrenaline, and other compounds having similar effects, should be reserved for emergencies and then used only with special caution.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : Will not burn
Auto decomposition : 632 °C (117 °F)

Other burning materials may cause "FREON" 22 to burn weakly.

Revised date 01.08.2024

Chlorodifluoromethane is not flammable at ambient temperatures and atmospheric pressure. However, chlorodifluoromethane has been shown in tests to be combustible at pressures as low as PSIG at ambient temperature when mixed with air at concentrations of 65 volume % air. Experimental data have also been reported which indicate the combustibility of "FREON" 22 in the presence of certain concentrations of chlorine.

Fire and Explosion Hazards:

Cylinders may rupture under fire conditions. Decomposition may occur.

Extinguishing Media

As appropriate for combustibles in the area. Extinguishing for other burning material in area is sufficient to stop burning.

Fire Fighting Instructions

Use water spray or fog to cool containers. A self-contained breathing apparatus (SCBA) is required if cylinders rupture or contents are released under fire conditions. Water runoff should be contained and neutralized before release.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Accidental Release Measures

Ventilate areas, especially low or enclosed places where heavy vapors might collect. Remove open flames. Use a self-contained breathing apparatus (SCBA) for large spills or releases.

HANDLING AND STORAGE

Handling (Personnel)

Use sufficient ventilation to keep employee exposure below recommended limits. "FREON" 22 should not be mixed with air for leak testing. In general, it should not be used or allowed to be present with high concentrations of air above atmospheric pressure. Contact with chlorine or other strong oxidizing agents should also be avoided.

Storage

Clean, dry area. Do not heat above 52 °C (125 °F).

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Revised date 01.08.2024

Normal ventilation for standard manufacturing procedures is generally adequate. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places.

Personal Protective Equipment

Impervious gloves and chemical splash goggles should be used when handling liquid.

Under normal manufacturing conditions, no respiratory protection is required when using this product.

A self-contained breathing apparatus (SCBA) is required if a large release occurs.

Exposure Guidelines

Applicable Exposure Limits

"FREON" 22 METHANE, CHLORODIFLUORO

PEL (OSHA) : None Established

TLV (ACGIH) : 1,000 ppm, 3,540 mg/m³, 8 Hr. TWA, A4

AEL * (DuPont) : None Established

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Boiling Point	: -40.8 C (-41.4 F)
Vapor Pressure	: 151 PSIG @ 25 °C (77 °F)
Vapor Density	: 3.03 (Air=1.0) @ 25 °C (77 °F)
% Volatiles	: 100 WT%
Evaporation Rate	: >1 (CCl ₄ =1.0)
Solubility in Water	: 0.3 WT% @ 25 °C (77 °F)
pH	: Neutral
Odor	: Slight ethereal
Form	: Liquefied Gas.
Color	: Clear, Colorless.
Liquid Density	: 1.194 g/cm ³ @ 25 °C (77 °F)

STABILITY AND REACTIVITY

Chemical Stability

Material is stable. However, avoid open flames and high temperatures.

Incompatibility with Other Materials

Incompatible with alkali or alkaline earth metals - powdered Al, Zn, Be, etc.

Revised date 01.08.2024

Decomposition

Decomposition products are hazardous. "FREON" 22 can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides. These materials are toxic and irritating. Contact should be avoided.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION

Animal Data

INHALATION:

4 hours, LC50, rat: 220,000 ppm.

Inhalation 4 hour, LC50, rat: 220,000 ppm

Animal testing indicates this material is a slight eye irritant.

Animal testing indicates this material is a skin irritant, but not a skin sensitizer.

Long-term exposure by ingestion caused no significant toxicological effects.

Single inhalation exposure to high doses caused central nerve depression. Inactivity or anesthesia, lung noise, altered respiratory rate, histopathological changes of the liver, cardiac sensitization, and potentially fatal disturbance of heart rhythm are associated with a heightened sensitivity to the action of epinephrine. Repeated exposure caused no significant toxicological effects. Long-term exposure caused reduced weight gain, and increased adrenals, kidney, liver, and pituitary weight.

In chronic inhalation studies, HCFC-22, at a concentration of 50,000 ppm (v/v), produced a small, but statistically significant increase of late-occurring tumors involving salivary glands in male rats, but not female rats or male or female mice. In the same studies, no increased incidence of tumors was seen in either species at concentrations of 10,000 ppm or 1000 ppm (v/v). Animal data show developmental effects only at exposure levels producing other toxic effects in the adult animal. This material is not considered a unique developmental hazard to the concepts. Reproductive data on male animals show no change in reproductive performance. Specific studies to evaluate the effect on female reproductive performance have not been conducted; however, limited information obtained from studies on developmental toxicity does not indicate adverse effects on female reproductive performance. This material produces genetic damage in bacterial cell cultures. In mammalian cell cultures and animals, this material has not produced genetic toxicity. In animal testing, this material has not caused permanent genetic damage in the reproductive cells of mammals (has not produced heritable genetic damage).

ECOLOGICAL INFORMATION

Eco toxicological Information

Aquatic Toxicity:

"FREON" 22

48 hour EC50 - Daphnia magna: 433 mg/L

Revised date 01.08.2024

DISPOSAL CONSIDERATIONS

Waste Disposal

Comply with Federal, State, and local regulations. Reclaim by distillation or remove to a permitted waste disposal facility.

TRANSPORTATION INFORMATION

Shipping Information

DOT/IMO
Proper Shipping Name : CHLORODIFLUOROMETHANE
Hazard Class : 2.2
UN No. : 1018
DOT/IMO Label : NONFLAMMABLE GAS

Shipping Containers

Tank Cars.
Tank Trucks.
Cylinders.

Shipping Information -- Canada

TDG
Proper Shipping Name : CHLORODIFLUOROMETHANE
PIN No. : 1018
TDG Class : 2.2

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : Reported/Included.
TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312
Acute : Yes
Chronic : No
Fire : No
Reactivity : No
Pressure : Yes

HAZARDOUS CHEMICAL LISTS

SARA Extremely Hazardous Substance : No
CERCLA Hazardous Substance : No
SARA Toxic Chemical - See Components Section

Canadian Regulations

Revised date 01.08.2024

CEPA Status : Compliant.
WHMIS Classification : CLASS A Compressed Gas

This product has been classified per the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

OTHER INFORMATION

NFPA, NPCA-HMIS

NPCA-HMIS Rating
Health : 1
Flammability : 0
Reactivity : 1

Personal Protection rating to be supplied by the user depending on use conditions

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or process.

End of MSDS
(Version August 2024)

Revised date 01.08.2024



HCC